

GUÍA DE SELECCIÓN DE EQUIPOS DE APLICACIÓN



		Ultimate MX II 695 ProContractor Series	Ultimate MX II 490 PC Pro	Nova 390 PC	190 Express PC	Boquillas Recomendadas, tamaño de orificio en pulgadas
Látex	Loxon XP	●	●			0.019 mm - 0.023 mm
	SuperPaint	●	●			0.017 mm - 0.021 mm
	Exterior Accents	●	●			0.017 mm - 0.021 mm
	ColorAccents	●	●			0.017 mm - 0.021 mm
	Sherotech 6000	●	●	●		0.017 mm - 0.021 mm
	Excello	●	●	●		0.015 mm - 0.021 mm
	Sherotech 4000	●	●	●	●	0.015 mm - 0.019 mm
	Colonial	●	●	●	●	0.015 mm - 0.019 mm
	Peninsular	●	●	●	●	0.015 mm - 0.017 mm
	Colorámica	●	●	●	●	0.015 mm - 0.017 mm
Selladores	Builders Base (Base Agua)	●	●	●	●	0.015 mm - 0.019 mm
	Builders Solution (Base Solvente)		●	●	●	0.015 mm - 0.019 mm
Impermeabilizantes	Aqualock 8000	●	●			0.021 mm - 0.023 mm
	Aqualock 6000	●	●	●		0.021 mm - 0.023 mm
	Aqualock 4000	●	●	●	●	0.017 mm - 0.021 mm
	Aqualock Bloqueador de Agua	●	●	●		0.021 mm - 0.023 mm
Anticorrosivos	Macropoxy 646 FC	●				0.017 mm - 0.023 mm
	Kem Cati Coat	●				0.017 mm - 0.023 mm
	Kem Kromik Univeral HS	●				0.017 mm - 0.021 mm
	Kem Faster Dry	●	●			0.015 mm - 0.021 mm
	Builders Base Anticorrosivo 6000 Rustop	●	●	●	●	0.013 mm - 0.017 mm
	Builders Base Anticorrosivo 4000 Colonial	●	●	●	●	0.013 mm - 0.017 mm
	Builders Base Anticorrosivo 2000 Estructural	●	●	●	●	0.013 mm - 0.017 mm
	Colorámica		●	●	●	0.013 mm - 0.017 mm
Esmaltes	Kem Enamel Poliuretano Industrial	●	●	●	●	0.011 mm - 0.015 mm
	Kem Lustral/Sistema 4000	●	●	●	●	0.011 mm - 0.015 mm
	Kem Faster Dry	●	●	●	●	0.011 mm - 0.015 mm
	Excello	●	●	●	●	0.011 mm - 0.015 mm
	Colonial	●	●	●	●	0.011 mm - 0.015 mm
	Peninsular	●	●	●	●	0.011 mm - 0.015 mm
	Colorámica	●	●	●	●	0.011 mm - 0.013 mm
Direct-to-Metal	Base Solvente	●	●	●	●	0.013 mm - 0.017 mm
	Base Agua	●	●	●	●	0.013 mm - 0.017 mm